

SATIN PLASTIC PAINT P-70

- **Characteristics:** Titanium dioxide and vinyl resin-based plastic paint with good coverage, ease of application and high gloss.
- **Indications:** Walls and ceilings both indoors and outdoors where a satin finish is desired. The finish is fully waterproof with extremely high resistance to the outdoors.
- **Application:** Brush, roller or spraying, directly to new untreated surfaces, or after previously restoring deteriorated paintwork (cracks, flaking, etc.).
Important: The application ambient temperature must not be lower than 5° C nor higher than 40° C. Do not apply if the weather is very humid and/or wet, or if frost is forecast before the product has been able to dry properly.
- **Thinning:** Water is used for thinning using 10/20 % for the first coats and 5/10% for finishes.

- **Technical characteristics:**

STORMER viscosity at 25°C	115 U.K.
Coverage	10 m ² to 12 m ² /litre
M.N.V. (fixed matter).....	38 %
Density	1.17 g/cc
Brushability	Excellent

Drying time: 20 to 30 minutes depending on the surface and the thickness applied. Allow a minimum of 2 hours to elapse before repainting.

Dry paint characteristics:

Persoz hardness 24 hours	116"
Gloss with angle of 45°	46%
Resistance to wet rubbing	Higher than 45,000 double wipes (Standard UNE 48284)
Resistance to dry rubbing	Good

Storage condition in the container: After storage for 6 months the paint maintains its initial characteristics.

- **Presentation format:** In containers holding 4 l and 15 l.
- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.