

## GLOSS SYNTHETIC ENAMEL

- **Indications:** Synthetic enamel for decorating and protecting a wide range of surfaces both indoors and outdoors (plaster, concrete, wood, iron, etc.). The formulation is alkyd resin-based with no yellowing, quick drying, good levelling properties and high gloss.
- **Application:** It can be applied using brushes, rollers or by spraying. In the case of metal surfaces and after having stripped the surface to be painted (sandpaper, sandblasting, etc.) apply a coat of QUICK DRYING ANTI-CORROSION PRIMER and enamel after 1 and a half hours. In the case of unvarnished wood, apply a coat of PRIMER-SEALER FOR WOOD and after 12 hours sand and enamel.
- **Thinning:** Thinning is carried out using W.S. or turpentine. The quantity of solvent depends on the application method chosen.

- **Technical characteristics:**

Oil type .....Safflower  
Specific weight .....1.25 g/cc  
Coverage .....10 m<sup>2</sup> to 12 m<sup>2</sup>/litre  
Viscosity .....210<sup>''</sup> Ford cup diameter 4 mm. 20° C.  
VOC content.....285 gr/litre

**Drying time:** On glass with a thickness of 90 wet microns at 20°C and 60% humidity.

Powder dry .....30 minutes  
Touch dry.....2 hours 30 minutes  
Hard dry .....7 hours

**Dry paint characteristics:**

Gloss with angle of 45° .....98%  
Persoz hardness 24 hours .....145<sup>''</sup>  
Persoz hardness 7 days .....225<sup>''</sup>

**Storage condition in the container:** After storage at room temperature for 6 months, no signs of sedimentation, skin or lumps and remains easy to mix.

- **Presentation format:** In containers holding 4 l and 750 cc. - 375 cc. - 125 cc.
- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.