

## GLOSS SYNTHETIC VARNISH

- **Indications:** Synthetic varnish with excellent coverage and brushability, particularly suited to decorating and protecting a wide range of wood types both indoors and outdoors. Great adherence properties even when applying very thin coats.
- **Application:** Easy to apply using brushes (high brushability) or by spraying. In the case of unvarnished wood first apply a grain filler, leave to dry for at least 15 hours and after sanding apply the GLOSS SYNTHETIC VARNISH.
- **Thinning:** Thinning is carried out using W.S. or turpentine. The quantity of solvent depends on the application method chosen.

- **Technical characteristics:**

Oil type ..... Soya  
Specific weight ..... 0.90 g/cc  
Coverage ..... 15 to 17 m<sup>2</sup>/litre  
Viscosity ..... 140" in cup 4 mm.  
VOC content.....390 gr/litre.

**Drying time:** On glass with a thickness of 90 wet microns at 20°C and 60% humidity.

Powder dry ..... 1 hour  
Touch dry ..... 2 hours 30 minutes  
Hard dry ..... 8 hours

**Dry varnish characteristics:**

Persoz hardness 24 hours ..... 112"  
Persoz hardness 7 days ..... 212"  
Adherence 7 days..... 100 %

**Storage condition in the container:** After storage for 6 months, it is easy to mix, with no skin, lumps or sediments.

- **Presentation format:** In containers holding 4 l and 750 cc. - 375 cc.

Note: The GLOSS SYNTHETIC VARNISH and the SATIN SEALER SYNTHETIC VARNISH are compatible with each other, therefore it is possible to obtain a wide range of gloss and satin finishes.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.