

HOGARPLAST PLASTIC PAINT

- **Characteristics:** Plastic paint for indoors, easy to apply, good coverage and excellent resistance to dry rubbing.
- **Indications:** Walls and ceilings indoors, both for new untreated surfaces or for repainting where a plastic finish is desired at a low cost.
- **Application:** Brush, roller or spraying, directly to new untreated surfaces or after previously restoring deteriorated paintwork (flakes, cracks, stains, etc.).
- **Thinning:** Water is used for thinning using approximately 10/15% for the first coats and 5/10% for finishes.

- **Technical characteristics:**

STORMER Viscosity at 25°C.....	130 U.K.
Coverage	5 to 6 m ² /litre
M.N.V. (fixed matter).....	62 %
Density	1.58 g/cc
Brushability	Good

Drying time: 20 to 30 minutes depending on the surface and the thickness applied. Allow 3 hours to elapse before applying a second coat.

Dry paint characteristics:

Persoz hardness 24 hours	158"
Gloss with angle of 45°	3%
Resistance to wet rubbing	23 double wipes (Standard UNE 48284)
Resistance to dry rubbing.....	Good

Storage condition in the container: After storage for 6 months the paint maintains its initial characteristics and is easy to mix simply by shaking.

- **Presentation format:** In containers holding 4 l and 13 l.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.