

SATIN SYNTHETIC VARNISH

- **Indications:** Dual purpose synthetic varnish with excellent coverage and brushability:
 - 1) It seals the grain of the unvarnished wood (grain filler) thus giving an even finish.
 - 2) With a second coat, and after sanding, the effect is a decorative satin varnish. This makes it perfect for all types of wood both indoors and outdoors.
- **Application:** Easy to apply using brushes (high brushability) or by spraying. Allow a minimum of 12 to 15 hours for sanding and the second coat.
- **Thinning:** Thinning is carried out using W.S. or turpentine. The quantity of solvent depends on the application method chosen.

□ **Technical characteristics:**

Oil type.....Soya
 Specific weight.....0.94 g/cc
 Viscosity120" Ford cup diameter 4 mm. 20° C
 ColourTransparent
 VOC contet.....290 gr/litre.

Drying time: On glass with a thickness of 90 wet microns at 20°C and 60% humidity.

Powder dry1 hour
 Touch dry.....2 hours 30 minutes
 Hard dry8 hours

Dry varnish characteristics:

Persoz hardness 24 hours160"
 Persoz hardness 7 days232"
 Adherence 7 days.....100 %

Storage condition in the container: After storage at for 6 months, it is easy to mix, with no skin, lumps or sediments.

- **Presentation format:** In containers holding 4 l and 750 cc. - 375 cc.

Note: The SATIN SEALER SYNTHETIC VARNISH and the GLOSS SYNTHETIC VARNISH are compatible with each other, therefore it is possible to obtain a wide range of gloss and satin finishes.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.