



SATIN WATER-BASED SYNTHETIC ENAMEL

CHARACTERISTICS: High quality water-based enamel with a satin finish, as well as excellent adherence, hardness and brushability. Formulated based on hydrosoluble alkyd and polyurethane resins, it offers the same resistance and permanence features as a solvent-based enamel.

APPLICATION: Ready to use. No thinning required.
Direct adherence on solvent-based enamels without requiring sanding.
Suitable for all kinds of outdoor and indoor surfaces, doors, windows, railings, walls etc.

TECHNICAL CHARACTERISTICS:

Resin type:.....Hydrosoluble polyurethane and alkyd resins
Density:..... 1.28 g/cc
Viscosity:.....5 and a half minutes Ford 4 cup
Coverage:8 to 10 m² per litre
Touch dry:.....3 hours at 20° C
Hard dry:24 hours
Repaint time:24 hours
Gloss angle 45°:40%
VOC content:0% - does not contain solvents

IMPORTANT: Do not apply at temperatures under 5° C or if frost or rain is forecast 24 hours after the application.

PRESENTATION FORMAT: Metal containers holding 4 l, 750 ml and 375 ml.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.