

GLOSS SYNTHETIC ENAMEL

INDICATIONS:

Synthetic enamel for decorating and protecting a wide range of surfaces both indoors and outdoors (plaster, concrete, wood, iron, etc.). The formulation is alkyd resin-based with no yellowing, quick drying, good levelling properties and high gloss.

APPLICATION:

It can be applied using brushes, rollers or by spraying. In the case of metal surfaces and after having stripped the surface to be painted (sandpaper, sandblasting, etc.) apply a coat of QUICK DRYING ANTI-CORROSION PRIMER and enamel after 6 and a half hours. In the case of unvarnished wood, apply a coat of PRIMER-SEALER FOR WOOD and after 24 hours sand and enamel.

THINNING:

Thinning is carried out using W.S. or turpentine, it is not recommended to use universal solvent. The quantity of solvent depends on the application method chosen.

TECHNICAL CHARACTERISTICS:

Oil type	Fatty acids
Specific weight	1.22 g/cc
Coverage	10 m ² to 12 m ² /litre
Viscosity	210" Ford cup diameter 4 mm. 20° C.
VOC content.....	285 gr/litre

Drying time: On glass with a thickness of 90 wet microns at 20°C and 60% humidity.

Touch dry.....	3 hours 30 minutes
Hard dry	10-12 days
Repaint time.....	24 h

Dry paint characteristics:

Gloss with angle of 45°	98%
Persoz hardness 24 hours	145"
Persoz hardness 7 days	225"

Storage condition in the container: After being stored at room temperature for 6 months, no signs of sedimentation, skin or lumps and remains easy to mix.

Presentation format: Metal containers holding 4 l, 750 ml, 375 ml, and 125 ml.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.