SATIN WHITE BASE ENAMEL

CHARACTERISTICS:
Synthetic enamel with excellent brushability and covering properties. Practically unchangeable colour and satin finish.

INDICATIONS:
Ideal for finishes for doors, windows etc. Where the decorator decides to include satin white instead of gloss paint.
It can also be used to paint kitchens and bathrooms to obtain extraordinary luminosity and washability features.

APPLICATION:
Ease of application for all kinds of surfaces using brushes, rollers or by spraying. On metal surfaces, after sanding or degreasing, it is recommendable to apply an undercoat of ANTI-CORROSION PRIMER. In the case of unvarnished new wood, it is worth applying a coat of PRIMER-SEALER FOR WOOD before applying the enamel.

THINNING:
Thinning is carried out using W.S. or turpentine, it is not recommended to use universal solvent. The quantity of solvent depends on the application method chosen.

TECHNICAL CHARACTERISTICS:

Oil type .....Fatty acids
Specific weight .....1,49 g/cc
Coverage .....10 m2 to 12 m2/litre
Viscosity .....240“ Ford cup diameter 4 mm. 20º C.
VOC content…….285 gr/litre

Drying time: On glass with a thickness of 90 wet microns at 20ºC and 60% humidity.

Touch dry.....3 hours
Hard dry .....10-12 days
Repaint time……..24 h

Dry paint characteristics:
Gloss with angle of 45º at 7 days.....34%
Persoz hardness 24 hours .....110“
Persoz hardness 7 days .....170“

Storage condition in the container: After being stored at room temperature for 6 months, no signs of sedimentation, skin or lumps and remains easy to mix.

Presentation format: Metal containers holding 4 l. and 750 ml.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.