

## ANTI-RUST GLOSS ENAMEL

**INDICATIONS:** Anti-rust water-based enamel to be applied directly to the oxide without the necessity of a previous primer. Gloss finish.

**APPLICATION:** Ready to use. Apply with no thinning. It is not necessary to remove the oxide, only the loose parts. Before the application, the surface must be clean and dry.  
Apply a minimum of 3 coats, leaving an interval from 2 to 3 hours between each coat.

**Important:** Do not apply the product with temperatures under 5° C nor above 35° C to avoid the risk of peeling. Do not apply it in full sun or if frost or rain is forecasted within 24h after the application.

### TECHNICAL CHARACTERISTICS:

Density .....	1.16 g /cc
Viscosity .....	4 minutes in a Ford cup diameter 4mm.
Coverage.....	from 4 to 5 m <sup>2</sup> / litre
Touch dry .....	30 minutes at 20° C
Hard dry .....	24 hours
Repaint time .....	3 hours
Gloss at an angle of 45°.....	95%
VOC content.....	30 gr/litre

**PRESENTATION FORMAT:** Metal containers holding 750 ml.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.