

## SATIN WATER-BASED SYNTHETIC ENAMEL

**CHARACTERISTICS:** High quality water-based enamel with a satin finish, as well as excellent adherence, hardness and brushability. Formulated based on hydrosoluble alkyd resins, it offers the same resistance and permanence features as a solvent-based enamel.

**APPLICATION:** Ready to use. No thinning required.

Direct adherence on solvent-based enamels without requiring sanding.

Suitable for all kinds of outdoor and indoor surfaces, doors, windows, railings, walls etc.

**IMPORTANT:** Do not apply at temperatures under 5° C nor more than 35° C to avoid cracks, not apply in full sun, or if frost or rain is forecasted within 24 hours after the application.

### TECHNICAL CHARACTERISTICS:

Resin type: ..... Hydrosoluble alkyd resin

Density: ..... 1.28 g/cc

Viscosity: ..... 5 and a half minutes Ford 4 cup

Coverage: ..... 8 to 10 m<sup>2</sup> per litre

Touch dry: ..... 3 hours at 20° C

Hard dry: ..... 24 hours

Repaint time: ..... 24 hours

Gloss angle 45°: ..... 40%

VOC content: ..... 0%

**PRESENTATION FORMAT:** Metal containers holding 4 l, 750 ml, 375 ml and 125 ml.

- The purpose of this leaflet is to provide information according to our criteria and experience. We accept no liability for the consequences of using these products since the circumstances of their application are beyond our control.